

# Product Information



A PRODUCT OF THE VALVOLINE COMPANY A DIVISION OF ASHLAND INC.

## VALVOLINE DURABLEND GREASE

DuraBlend Grease is a semi-synthetic lithium complex EP heavy-duty automotive grease with exceptional resistance to high temperatures and heavy loads. It is recommended for a wide range of industrial, automotive, mining and fleet applications including wheel bearings of disc-brake equipped vehicles and constant velocity joints.

Character: Smooth, buttery, water repellent, oxidation & rust inhibited, extreme pressure

---

### Approvals/Performance Levels

---

General Motors Part No. 1051344 (which supersedes GM Part No. 1051195)  
NLGI GC- LB

---

### Typical Properties

---

NLGI Grade	2
Soap Base	Lithium Complex
Color	Blue
ASTM Worked Penetration @ 77°F	275
ASTM Dropping Point, °F	545
Kinematic Vis @ 40° C, cSt	129.5
Kinematic Vis @ 100° C, cSt	14.5
Viscosity Index	110
Pour Point °C	-18
Timken OK Load, lbs min	50

This information only applies to products manufactured in the following location(s): USA, Canada.

Effective Date:	Replaces:	Author's Initials:	Code
07-08-03	07-28-98	DJD	