

# Product Information



A PRODUCT OF THE VALVOLINE COMPANY A DIVISION OF ASHLAND INC.

## VALVOLINE HIGH PERFORMANCE SNOWMOBILE LUBRICANT

**Valvoline High Performance Snowmobile Lubricant** is a superior two-cycle lubricant formulated with premium base stocks and a carefully selected ashless additive system. It is pre-diluted for ease of mixing with gasoline at low ambient temperatures and may be used in injector systems.

This product is recommended for two-cycle snowmobile engines operating under high speed, high load and high temperature engine conditions. It meets the requirements of snowmobile engine manufacturers who recommend a NMMA/BIA TC-W3 approved oil.

**High Performance Snowmobile Lubricant** is recommended for the following builders of snowmobiles:

Artic Cat, Chrysler, Canadian Curtis-Wright, Cuyuna, Kawasaki, Evinrude, Hirth, Husqvarna, JLO, Johnson, Kohler 2-Cycle, Lloyd LS 400, Motosacoche, OMC, Rockwell-JLO, Rotax, Rupp, Star Polaris-TX, Mercury, Kioritz, Suzuki, Wisconsin, Hirth and Yamaha.

\* Manufacturers recommendation varies for different models.

---

### Typical Properties

---

|                        |            |
|------------------------|------------|
| Gravity (API)          | 32.8       |
| Vis @ 100°C (cSt)      | 7.60       |
| CCS - cP (°C)          | 5450(-25C) |
| Pour Point, °C max     | -40        |
| Sulfated Ash, wt%      | Nil        |
| Color                  | Blue-Green |
| Flash Point (D-93), °C | 65         |
| TBN (D-2896)           | 3.60       |

This information only applies to products manufactured in the following location(s): USA, Canada.

Effective Date:  
07-08-03

Replaces:  
07-29-98

Author's Initials:  
DJJ

Code