

Product Information



A PRODUCT OF THE VALVOLINE COMPANY A DIVISION OF ASHLAND INC.

MAXLIFE™ DEX/MERC ATF

Valvoline MaxLife™ DEX/MERC ATF (Automatic Transmission Fluid) is the first fluid of its kind that is specifically formulated for today's technologically sophisticated automatic transmissions. It is formulated with premium base stocks, unique seal conditioners, long-life friction modifiers, special anti-wear additives, and shear stable viscosity modifiers, among other performance packages, to fight the four major causes of transmission breakdown, including leaks, slippage, shudder and gear wear. Valvoline MaxLife™ DEX/MERC ATF is recommended for use in most new and rebuilt transmissions and will not void new car warranties.

The Valvoline MaxLife™ DEX/MERC ATF Advantages:

- Synthetic fluid
- Condition transmission seals to prevent leaks
- Reduce varnish formation and wear
- Improve and maintain smooth shifting longer than conventional automatic transmission fluids
- Provide excellent flow properties at low temperatures and greater film protection at high temperatures
- Maximize the life of higher mileage transmissions

Performance Levels

Exceeds the latest performance requirements of DEXRON®-III H and MERCON® fluids

Recommended for use in GM, Ford, Mazda, Toyota, Hyundai and others where DEXRON®-III and MERCON® fluids are specified

Suitable for use in MERCON®V, MERCON®SP and MERCON®LV applications

Suitable for use in DEXRON®-VI applications

Suitable for use in Nissan and Infiniti Matic D, Matic J, Matic K, and Matic S applications

Suitable for use in KIA SP-II and SP-III applications and in Mitsubishi Diamond SP-II and SP-III applications

Suitable for use in Toyota/Lexus Type T, T-III, T-IV and WS (except hybrids) applications

Suitable for use in Honda/Acura ATF-Z1 (except in CVTs) applications

Suitable for use in Allison C4, TES-295 and TES-389 applications

Suitable for use in Mercedes Benz NAG1 applications

Suitable for use in Volvo passenger car applications and STD 1273.41

Suitable for use in Volkswagen TL52162

Suitable for use in H55.6335.33(G607) and H55.6335.33(G1363) applications

<u>Test</u>	<u>Typical Property</u>
Viscosity @ 100°C, cSt	6.3
Viscosity @ 40°C, cSt	30.3
Viscosity Index	165
Specific Gravity @ 60°F	0.85
Pour Point, °C,	-51
Brookfield Viscosity @ -40°C, cP	12,000
Flash Point, COC, °C	202
ASTM Color	5
Appearance	Red