

# Product Information



A PRODUCT OF THE VALVOLINE COMPANY A DIVISION OF ASHLAND INC.

## MAXLIFE™ DEX/MERC ATF

Valvoline MaxLife™ DEX/MERC ATF (Automatic Transmission Fluid) is the first fluid of its kind that is specifically formulated for today's technologically sophisticated automatic transmissions. It is formulated with premium base stocks, unique seal conditioners, long-life friction modifiers, special anti-wear additives, and shear stable viscosity modifiers, among other performance packages, to fight the four major causes of transmission breakdown, including leaks, slippage, shudder and gear wear. Valvoline MaxLife™ DEX/MERC ATF is recommended for use in most new and rebuilt transmissions and will not void new car warranties.

### The Valvoline MaxLife™ DEX/MERC ATF Advantages:

- Synthetic fluid
- Condition transmission seals to prevent leaks
- Reduce varnish formation and wear
- Improve and maintain smooth shifting longer than conventional automatic transmission fluids
- Provide excellent flow properties at low temperatures and greater film protection at high temperatures
- Maximize the life of higher mileage transmissions

### Performance Levels

Exceeds the latest performance requirements of DEXRON®-III H and MERCON® fluids

Recommended for use in GM, Ford, Mazda, Toyota, Hyundai and others where DEXRON®-III and MERCON® fluids are specified

Suitable for use in MERCON®V, MERCON®SP\* and MERCON®LV\* applications

Suitable for use in DEXRON®-VI\* applications

Suitable for use in Nissan and Infiniti Matic D, Matic J, Matic K, and Matic S applications

Suitable for use in KIA SP-II and SP-III applications and in Mitsubishi Diamond SP-II and SP-III applications

Suitable for use in Toyota/Lexus Type T, T-III, T-IV and WS\* applications

Suitable for use in Honda/Acura ATF-Z1 (except in CVTs) applications

Approved for use where Allison C4 is specified, suitable for use in Allison TES-295 and TES-389 applications

Suitable for use in Mercedes Benz 236.x applications

Approved for use where Volvo 1273.41 is specified, suitable for use in Volvo passenger car applications

Suitable for use in Volkswagen TL52162

Approved for use where Voith H55.6335.33(G607) is specified, suitable for use in H55.6335.33(G1363) applications

\* Viscosity requirement is not met.

<u>Test</u>	<u>Typical Property</u>
Viscosity @ 100°C, cSt	7.25
Viscosity @ 40°C, cSt	35.1
Viscosity Index	177
Specific Gravity @ 60°F	0.8471
Pour Point, °C,	-51
Brookfield Viscosity @ -40°C, cP	12,500
Flash Point, COC, °C	202
ASTM Color	5
Appearance	Red