

Product Information



A PRODUCT OF THE VALVOLINE COMPANY A DIVISION OF ASHLAND INC.

VALVOLINE OUTBOARD EP GEAR OIL

Valvoline Outboard EP Gear Oil is a special lubricant that is formulated with premium base stocks and select additives to provide excellent performance. It is a moderate duty sulfur phosphorus extreme pressure gear oil. Valvoline Outboard EP Gear Oil meets the requirements of a API GL-3 and GL-4. It is recommended for use in Aeromarine, Bearcat, Clinton, Eska, Evinrude, Honda, Johnson, Mariner, McCulloch, Mercury, Sears, Suzuki, Triton, Wizard, Yamaha or wherever an extreme pressure lubricant is specified by outboard equipment manufacturers for their gear units.

The Valvoline Outboard EP Gear Oil Advantage:

- Excellent extreme pressure properties
- Good oxidation resistance
- Excellent corrosion resistance

Approvals/Performance Levels

Meets requirements of API GL-3 & GL-4

Test	Typical Property
API Gravity @ 60F	24.2
Viscosity @ 100C, cSt	14.5
Brookfield Viscosity @ -26C, cP	<150,000
Viscosity Index	95
Pour Point, C, max.	-27

Part Numbers

Size
Size
Size
Size

This information only applies to products manufactured in the following location(s):

Effective Date:	Replaces:	Author's Initials:	Pages	Code
07-08-03		DJD		