

Product Information



A PRODUCT OF THE VALVOLINE COMPANY A DIVISION OF ASHLAND INC.

PYROIL SILICONE LUBRICANT SPRAY PART NO. SLS-10, SLS-5, SLS-54

- Lubricates
- Stops Squeaks and Sticking
- Non-Staining
- Waterproofs and Protects
- Stops Freezing of Trunk Lids, Doors, and Locks
- Leaves No Sticky Residue

Silicone Polymer

Pyroil Silicone Lubricant Spray produces a thin, non-oily, non-staining polymer film that lubricates, waterproofs, and protects. **Pyroil Silicone Lubricant Spray** is not designed to leave surface glossy. High gloss is attained by increasing the viscosity of the silicone polymer. Unfortunately, high-viscosity, high-gloss silicone polymers produce a thick film that tends to remain sticky and attract dust and dirt. Lower-viscosity silicone polymers tend to penetrate into small openings, providing lubrication and protection, leaving no stains or sticky mess.

Applications

Pyroil Silicone Lubricant Spray should be used to lubricate door hinges, rubber mountings, drawers, windows, sliding doors, dies, etc. Waterproofs ignitions systems, garden tools, fishing equipment, firearms, and leather boots. Since surfaces treated with **Pyroil Silicone Lubricant Spray** repel water; trunk lids, doors, and locks can be protected from freezing.

Easy To Use

For large, open areas; simply hold can upright 4-6 inches from the surface and spray. An extension tube is provided for hard-to-reach areas.

Technical Data:

Appearance	Clear Liquid
Propellant	Hydrocarbon

Caution: Contains petroleum distillates and silicone polymer, extremely flammable.

This information only applies to products manufactured in the following location(s): USA, Canada.

Effective Date:	Expiration Date:	Replaces:	Author's Initials:	Code
03-01-04	06-01-08		RJB	