

Product Information

A PRODUCT OF VALVOLINE, A DIVISION OF ASHLAND INC.



Valvoline® Waylube Oils

Valvoline's Waylube Oils are stable, high quality oils specially compounded to provide efficient lubrication of machine ways. They are adhesive, tacky and resist stick-slip, thereby assuring smooth, efficient operation. These products have excellent extreme pressure and film-strength properties.

Approvals	ISO Viscosity Grade
Cincinnati Milacron P-53	32
Cincinnati Milacron P-47	68
Cincinnati Milacron P-50	220

Typical Properties	ISO 32	ISO 68	ISO 150	ISO 220
Gravity, degree API	31.7	30.2	27.4	30.0
Flash Point - COC °F	430	435	485	490
Fire Point - COC °F	470	475	510	535
Viscosity @ 100° F SUS	135-165	284-346	800-900	900-1100
Viscosity @ 210° F SUS	43	56	84	91
Viscosity Index Min.	95	-5	104	95
Pour Point °F	0	+10	+5	+10
Corrosion	Neg.	Neg.	Neg.	Neg.
C.M. Spec.	P-53	P-47		P-50

Typical Properties	
Bulk	VV702640
55 Gallon Drum	VV70264

Refer to Valvoline Inc.'s Material Safety Data Sheet for health and safety information.

This information only applies to products manufactured in the following location(s): USA, Canada.

Effective Date:	Expiration Date:	Replaces:	Author's Initials:	Code
09/27/2007	N/A	07/05/2001	JH	PI 0701

ASHLAND