

# Product Information



A PRODUCT OF VALVOLINE, A DIVISION OF ASHLAND INC.

## Valvoline's Premium Blue<sup>®</sup> GEO LA

Valvoline's Premium Blue GEO LA is a low ash SAE 40 engine oil recommended for use in stationary high output, highly turbocharged, spark ignited natural gas engines. It is formulated with premium quality paraffinic basestocks and additive components to provide outstanding lubrication of gaseous fueled engines. The ash content of the oil is minimized to reduce spark plug fouling and formulation of combustion chamber "hot-spots" that can lead to increased No<sub>x</sub> formation and detonation. This product is approved by Cummins for use in Cummins QSV 81/91 Series engines. It is formulated to meet the requirements of Cummins roller-follower natural gas engines in stationary service, and other natural gas engines, including Dresser-Rand Category III, Caterpillar natural gas engines, Waukesha Co-Generation requirements. For other engines, please refer to engine manufacturer's specifications.

### Premium Blue<sup>®</sup> GEO LA Advantages:

- Reduced ash content
- Valve recession protection
- Low oil consumption and piston deposit control
- Advanced oxidation control
- Superior nitration control
- Excellent NSCR catalyst compatibility
- Enhanced protection from corrosion

Typical Properties	SAE 40
Gravity, degree API	29.5
Specific Gravity	.8786
Viscosity @ 40° C, cSt	131.64
Viscosity @ 100° C, cSt	14.03
Viscosity Index	103
Zinc, ppm	310
Phosphorus, ppm	280
Calcium, ppm	1200
Pour Point, °C	-36
Flash Point, COC, °C	266
Total Base Number (D-2896)	5.5
Sulfated Ash, Wt. %	0.44

  

Part Numbers	
Bulk	VV705230
55 Gallon Drum	VV70523

Endorsed and Recommended by Cummins Inc.



Refer to Valvoline's Material Safety Data Sheet for health and safety instructions

This information only applies to products manufactured in the following location(s): North America.

Effective Date:	Expiration Date:	Replaces:	Author's Initials:	Code
06/26/2009	N/A	05/07/2009	JH	PI 0902

**ASHLAND**