

Product Information

PYROIL

A PRODUCT OF THE VALVOLINE COMPANY A DIVISION OF ASHLAND INC.

PYROIL Automatic Transmission Fluid With Stop Leak PART NO. ATFS-32

- **Help Stop Leaks**
- **Helps Transmission Run Smoothly and Efficiently**
- **Compatible with all Vehicles requiring a Dexron[®] III Fluid**
- **Compatible with all Vehicles requiring a Mercon[®] Fluid**

A Must for Maintaining Automatic Transmissions

Rubber seals and “O” rings used in automatic transmissions contain plasticizers which make seals soft and pliable. Plasticizers normally contribute between four and seven percent to the volume of rubber seals. Hot transmission fluid can remove plasticizers from seals and “O” rings, causing them to become hard and brittle. Removing plasticizers can also causes seals to shrink allowing transmission fluid to leak. **Pyroil Automatic Transmission Fluid With Stop Leak** is a premium blended transmission fluid with an advanced stop leak additive, specially formulated to help condition and revitalize dried, shrunken and hardened seals. **Pyroil Automatic Transmission Fluid With Stop Leak** provides excellent protection against wear and high temperature breakdown.

Pyroil Automatic Transmission Fluid With Stop Leak is compatible with all GM, Ford (except where a Ford Mercon[®] V of Type F “M2C33-F or G fluid is recommended).

This lubricant is also compatible with Honda, Nissan, Toyota, Subaru and other imported vehicles requiring a Dexron[®] III/Mercon[®] Fluid.

One bottle of **Pyroil Automatic Transmission Fluid With Stop Leak** should be added to each 10 quarts of transmission fluid. For best results, use Valvoline Automatic Transmission Fluid. Do not exceed manufacturer’s recommended capacity level. Do not use as a substitute for Transmission Fluid.

This information only applies to products manufactured in the following location(s): USA, Canada.

Effective Date:	Expiration Date:	Replaces:	Author's Initials:	Code
2000-09-25	2002-09-25		TRS	